

WhisperCeiling™ Fan - Quiet, Spot Ventilation Solution, 80 CFM

FV-08VQ5

MORE DETAILS

Product Family Name WhisperCeiling

Air Volume Exhaust (CFM) 80 @ 0.1" SP, 62 @ 0.25" SP

Noise (Sones) 80 @ 0.1" SP = less than 0.3, 62 @ 0.25" SP = 0.4

Power Consumption (Watts) 14.7W

Energy Efficiency (CFM/Watt) 5.8 CFM/W

Current (Amps) 0.12A

Power Rating (V/Hz) 120/60

Motor Type (AC/DC) AC

Duct Diameter 4" & 6"

Installation Ceiling

Radiation Damper Available Yes

Mounting Opening (in sq.) 10-1/2"

Grille Size (in sq.) 13"

ENERGY STAR® Certified Yes

Other Approved Codes and Standards ASHRAE 62.2, LEED, California Title 24, Washington VIAQ

UL Listed for Tub/Shower Enclosure when used with a GFCI Protected Circuit Yes

Warranty 3 Year Parts,

Master Carton Dimensions (HxWxD) 16-15/16" x 14-5/16" x 11-1/16"

Master Carton Gross Weight (lbs.) 10.4

UPC885170005600
