

Revolv[®] RG7 95%+ AFUE Gas Furnaces

WITH COIL CABINET



WITHOUT COIL CABINET



High Efficiency: 95%+ AFUE.

Sealed Combustion: Can be vented vertically or horizontally with PVC pipe.

Vents Exhaust Gases: Directly outdoors and draws in outside fresh air for combustion.

Choice of Models: For up to 4 tons A/C and 3.5 tons H/P.

Modern Hot Surface Ignition: No pilot light to blow out.

Multi-Speed Direct Drive Blower.

Low Maintenance: Sealed bearings on motors, reliable controls and burners.

Appliance Quality Metal Door: With baked enamel finish for long life and easy cleaning.

COIL CABINET

911969A (20") or 922594 (26")



Warranty

2 Years Parts / 1 Year Labor

10 Years Heat Exchanger

Visit www.stylecrestinc.com
for warranty registration

Today's changing government standards are making it more difficult than ever to find the right matching equipment for Manufactured homes...

We have the answers!

Furnace Model Number	Description	Depth (D)	Width (W)	Height (H)	Input MBtuh	Output MBtuh	A/C Ready Tons	Shipping Weight (lbs)
RG7D45N4	RG7 95%+ Downflow GAS 45KBTU No Cabinet, 4 Ton Blower*	23-3/4"	19-7/8"	56"	45	42.75	4	150
RG7D60N4	RG7 95%+ Downflow GAS 60KBTU No Cabinet, 4 Ton Blower*	23-3/4"	19-7/8"	56"	60	57	4	150
RG7D72N4	RG7 95%+ Downflow GAS 72KBTU No Cabinet, 4 Ton Blower*	23-3/4"	19-7/8"	56"	72	68.4	4	155
RG7D45C4	RG7 95%+ Downflow GAS 45KBTU With Cabinet, 4 Ton Blower	23-3/4"	19-7/8"	76"	45	42.75	4	170
RG7D60C4	RG7 95%+ Downflow GAS 60KBTU With Cabinet, 4 Ton Blower	23-3/4"	19-7/8"	76"	60	57	4	170
RG7D72C4	RG7 95%+ Downflow GAS 72KBTU With Cabinet 4 Ton Blower	23-3/4"	19-7/8"	76"	72	68.4	4	175

*For cooling and heat pump applications, add coil cabinet 91196A (20") or 922594 (26")

Accessories for RG7 95%+ AFUE Gas Furnaces		Clearances		
Description	Part Number	All Models	Closet	Alcove
Coil Cabinet (20"H)	911696A	Front	1"	1"
Coil Cabinet (26" H)	922594	Back	0"	0"
Side Return Air Kit	904003	Sides	0"	0"
Neutralizer Kit - All Models	902377	Vent	0"	0"
PVC Isolation Kit	904063	Top	6"	6"
Vent Transition Kit	904106	Duct (Plenum w/coil box)	0"	0"
Concentric Vent Termination Kit (for horizontal and vertical venting)	904953	Duct (Plenum w/o coil box) within 3 feet	1/4"	1/4"

VENTING: All models are approved for both vertical and horizontal direct (2 pipe) venting applications. See Vent Table below for specified sizes and allowable lengths

Maximum Direct Vent, Dual Pipe Length (ft.)*

RG7 Inputs (BTUH)	Inlet/Outlet 3 in. Diameter	Inlet/Outlet 2 in. Diameter
45,000	60	30
60,000	60	30
72,000	60	30

*NOTES: Subtract 3.5 ft. for each additional 3" 90 degree elbow. • Two 45 degree elbows are equivalent to one 90 degree elbow. One short radius elbow is equivalent to two long radius elbows. • Do not include termination elbows in calculation of vent length. This table is applicable for elevations from sea level to 2,000 ft. • For higher elevations decrease vent pipe lengths by 8% per 1000 ft. of altitude. Only the listed pipe materials are approved for use with RG7 condensing furnaces. • For Canadian applications, use ULC S636 approved material.

DIMENSIONS

