Material Safety Data Sheet

0816/0826/0810 Series Spec Compliant Silicone Sealant – Acetoxy Cure - Clear, White & Colors

MSDS No. 0081 Rev. 5

Emergency Phone No. 800-535-5053 - INFOTRAC

	-	_	_		_	3-3033 - IINI	
	SECTION 1 – P	RODUCT NAME &	MANUFACTURER 1	INFORM	ATION		
PRODUCT NAME	Silicone Sealant – Clear & All Colors						
MANUFACTURER'S N TELEPHONE NUMBER							
STREET ADDRESS	4175 Webb Street						
CITY / STATE / ZIP	CITY / STATE / ZIP Pryor, Oklahoma 74361						
SECTIO	ON 2 – COMPOSITI	ON/HAZARDOUS	INGREDIENTS	%	TLV	PEL	UNITS
PRODUCT CONSISTS	OF:						
Ethyltriacetoxysilane (17689-77-9)				< 6%	NE	NE	
Methyltriacetoxysilane ** (4253-34-3)				< 6%	10	10	ppm
Titanium Diox	ride *** (13463-67-7) (In white	& colors only)		< 5%	10	15	mg/m3
Silica, amorph	ous *** (7631-86-9)			< 13	20	20	mg/m3
Hydroxy-termi	inated Dimethyl siloxane (70131	-67-8)		> 50	10	10	ppm
Polydimethylsiloxane (63148-62-9)				< 10	10	10	ppm
1 org announg ion	100,4410						PP
Non-hazardous ingredients*				> 10	NA	NA	
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Observe limits for acetic acid formed during curing on exposure to water or humid air. ***Inhalation of particulates unlikely due to product's physical state. Calculated VOC: <3%/wt (<40 g/L). CARB Compliance: Yes. Prop 65 Ingredients: None.							
	S	ECTION 3 – HAZAR	DS IDENTIFICATION	ON			
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	Skin Absorption	Eye Contact	⊠ Inhala	tion	⊠ Inge	estion
EMERGENCY OVERVIEW Clear/opaque or colored paste. Harmful if swallowed or absorbed through skin. May cause eye & skin irritation. May cause nose, throat & respiratory tract irritation.							
EFFECTS OF OVEREXPOSURE Acute: (Eye) – Direct contact may cause moderate irritation. (Skin) – May cause moderate irritation. (Inhalation) – Slight irritation to respiratory passages. (Oral) – No significant effects expected from a single short-term exposure. Prolonged/Repeated Exposure: No known applicable information.							
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.						
		SECTION 4 – FIRS	ST AID MEASURES				
SKIN CONTACT Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.							
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.						
INHALATION	No first aid should be needed under normal use. Remove to fresh air if needed.						
INGESTION	Not intended for ingestion. No first aid should be needed. Get medical attention if irritation persists. Treat according to person's condition & specifics of exposure.						

SECTION 5 – FIRE FIGHTING MEASURES						
FLAMMABLE Yes No						
EXTINGUISHING Carbon Dioxide, Dry Chemical, Foam, Water Spray						
MEDIA FLASHPOINT (°F) & METHOD	> 212 (Closed Cup)	UPPER EXPLOSIVE (% BY VOLUME)	E LIMIT NE			
LOWER EXPLOSIVE LIMI' (% BY VOLUME)	n NE	AUTOIGNITION TEMPERTURE (°F)	NE			
UNUSUAL FIRE & EXPLOS HAZARDS	ION None					
SPECIAL FIREFIGHTING PROCEDURES Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces. Thermal breakdown of this product during fire or high heat conditions may evolve the following hazardous decomposition products: Silicon dioxide. Carbon oxides & traces of incompletely burned carbon compounds. Formaldehyde.						
	SECTION 6 - ACCIDE	NTAL RELEAS	SE MEASURES			
PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.						
	SECTION 7 – HA	ANDLING & ST	ORAGE			
HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use w/ adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use appropriate respirator. Avoid eye contact. Avoid skin contact.						
STORAGE REQUIREMENT	STORAGE REQUIREMENTS Keep container closed & store away from water or moisture. Avoid extreme heat or cold. Store away from oxidizing materials. When heated to temperatures above 300F in presence of air, product may form formaldehyde vapors.					
SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION						
RESPIRATORY No respiratory protection should be needed. As Engineering Controls, Local & General Ventilation is recommended. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm & ACGIG TLV: TWA 10 ppm, STEL 15 ppm. Use respiratory protection if adequate local exhaust ventilation unavailable. OSHA respirator regulations 29 CFR 1910.134 should be followed, using NIOSH/MSHA approved respirators. Spills: Full face respirator.						
exhai	st ventilation unavailable. OSHA respirator regulations 2					
exhai face i	st ventilation unavailable. OSHA respirator regulations 2					
exhat face t EYEWEAR Gogg	ast ventilation unavailable. OSHA respirator regulations 2 espirator.					
exhat face of EYEWEAR Gogg CLOTHING / GLOVES Nitril	ast ventilation unavailable. OSHA respirator regulations 2 espirator. les or safety glasses w/ side shields. Avoid eye contact.	9 CFR 1910.134 should I	be followed, using NIOSH/MSHA approved respirators. Spills: Full			
exhat face to EYEWEAR Gogg CLOTHING / GLOVES HYGENIC Reme	ast ventilation unavailable. OSHA respirator regulations 2 espirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact.	9 CFR 1910.134 should be s	ne followed, using NIOSH/MSHA approved respirators. Spills: Full			
exhat face to EYEWEAR Gogg CLOTHING / GLOVES HYGENIC Reme	ast ventilation unavailable. OSHA respirator regulations 2 espirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash ha	9 CFR 1910.134 should be s	ne followed, using NIOSH/MSHA approved respirators. Spills: Full			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES Remo	ast ventilation unavailable. OSHA respirator regulations 2 respirator. les or safety glasses w/ side shields. Avoid eye contact. rubber or butyl rubber gloves. Avoid skin contact. vee & wash contaminated clothing before re-use. Wash has SECTION 9 – PHYSICAL	9 CFR 1910.134 should be unds before breaks & @ e AND CHEMIC ODOR &	ne followed, using NIOSH/MSHA approved respirators. Spills: Full and of workday. AL PROPERTIES			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES PHYSICAL STATE	ast ventilation unavailable. OSHA respirator regulations 2 espirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash ha SECTION 9 – PHYSICAL Viscous paste	9 CFR 1910.134 should be and should be an and should be an	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES PHYSICAL STATE SPECIFIC GRAVITY	ast ventilation unavailable. OSHA respirator regulations 2 espirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash ha SECTION 9 – PHYSICAL Viscous paste Approximately 1.0 to 1.1	9 CFR 1910.134 should be and should be an and should be an	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor NE			
EYEWEAR Gogg CLOTHING / GLOVES Nitril GLOVES REMOTE HYGENIC PRACTICES PHYSICAL STATE SPECIFIC GRAVITY EVAPORATION RATE	ast ventilation unavailable. OSHA respirator regulations 2 respirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash has SECTION 9 – PHYSICAL Viscous paste Approximately 1.0 to 1.1 NE	ands before breaks & @ e AND CHEMIC ODOR & APPEARANCE VAPOR DENSITY (AIR=1) BOILING RANGE (°F) SOLUBILITY IN	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor NE NE			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES PHYSICAL STATE SPECIFIC GRAVITY EVAPORATION RATE PH VAPOR PRESSURE (MM	ast ventilation unavailable. OSHA respirator regulations 2 respirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash has SECTION 9 – PHYSICAL Viscous paste Approximately 1.0 to 1.1 NE NE	ands before breaks & @ e AND CHEMIC ODOR & APPEARANCE VAPOR DENSITY (AIR=1) BOILING RANGE (°F) SOLUBILITY IN WATER %/WT VOLATILE (TNV)	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor NE NE NE NE			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES PHYSICAL STATE SPECIFIC GRAVITY EVAPORATION RATE PH VAPOR PRESSURE (MM	ast ventilation unavailable. OSHA respirator regulations 2 respirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash has SECTION 9 – PHYSICAL Viscous paste Approximately 1.0 to 1.1 NE NE NE SECTION 10 – STAI	ands before breaks & @ e AND CHEMIC ODOR & APPEARANCE VAPOR DENSITY (AIR=1) BOILING RANGE (°F) SOLUBILITY IN WATER %/WT VOLATILE (TNV)	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor NE NE NE NE			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES PHYSICAL STATE SPECIFIC GRAVITY EVAPORATION RATE PH VAPOR PRESSURE (MM Hg)	ast ventilation unavailable. OSHA respirator regulations 2 espirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash ha SECTION 9 – PHYSICAL Viscous paste Approximately 1.0 to 1.1 NE NE NE SECTION 10 – STAI Yes \[\begin{small} NO \] Stable under normal conditions.	ands before breaks & @ e AND CHEMIC ODOR & APPEARANCE VAPOR DENSITY (AIR=1) BOILING RANGE (°F) SOLUBILITY IN WATER %/WT VOLATILE (TNV) BILITY AND R	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor NE NE NE NE			
EYEWEAR Gogg CLOTHING / GLOVES HYGENIC PRACTICES PHYSICAL STATE SPECIFIC GRAVITY EVAPORATION RATE PH VAPOR PRESSURE (MM Hg)	sist ventilation unavailable. OSHA respirator regulations 2 respirator. les or safety glasses w/ side shields. Avoid eye contact. e rubber or butyl rubber gloves. Avoid skin contact. ove & wash contaminated clothing before re-use. Wash has SECTION 9 – PHYSICAL Viscous paste Approximately 1.0 to 1.1 NE NE NE SECTION 10 – STAF Yes No Stable under normal conditions. Yes No Materials to Avoid: W	ands before breaks & @ e AND CHEMIC ODOR & APPEARANCE VAPOR DENSITY (AIR=1) BOILING RANGE (°F) SOLUBILITY IN WATER %/WT VOLATILE (TNV) BILITY AND R	nd of workday. AL PROPERTIES Clear or colored paste w/ acetic acid odor NE NE NE NE NE NE NE NE NE N			

	SECTION 11 - TOXICOLOGICAL INFORMATION / CARCINOGENICITY
ACGIH	No known applicable information. This product does not contain carcinogens (@0.1% or greater) as defined by IARC, NTP or OSHA.
OSHA	No known applicable information. See above.
IARC	No known applicable information. See above.
NTP	No known applicable information. See above.
DATA WITH POSSIBLE RELEVANCE TO HUMANS	No known applicable information. See above.

SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY Complete information is not yet available.

Ecotoxicity Classification Criteria:

Hazard Parameters (LC50 or EC50) High Medium Low

Acute Aquatic Toxicity mg/L <= 1 >1 & <= 100 >100

Acute Terrestrial Toxicity <= 100 >100 & <=2000 >2000

(Table adapted from "Environmental Toxicology & Risk Assessment", ASTM STP 1179, p. 34, 1993)

(Table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Dispose of material in accordance w/ Federal, State & Local regulations.

EPA WASTE CODE IF DISCARDED (40CFR Sec.261) None. RCRA Hazard Class (40 CFR 261): Not classified as a hazardous waste. State or local laws may impose additional regulatory requirements

regarding disposal.

SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION <u>DOT Road Shipment Information (49 CFR 172.101):</u> Not subject to DOT. <u>Ocean Shipment (IMDG)</u>: Not subject to IMDG code. <u>Air Shipment (IATA)</u>: Not subject to IATA regulations.

SECTION 15 – REGULATORY INFORMATION						
CERCLA – SARA HAZARD CATEGORY	Section 304 CERCLA: None. Section 302 (Extremely Hazardous Substances): None. Section 312 (Hazard Class): Acute: Yes. Chronic: No. Fire: No. Pressure: No. Reactive: No.	U.S. STATE REGS	See Section 16.			
SARA 313	None present or none present in regulated quantities.	TSCA	All ingredients either on TSCA Inventory or exempt.			

SECTION 16 - OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

Prop 65 Ingredients: (Known to State of California to cause cancer) None. NJ Right-to-Know: (Top 5 Ingredients): Hydroxy-terminated Dimethyl Siloxane (70131-67-8), Silica, amorphous (7631-86-9), Methyltriacetoxysilane (4253-34-3), Ethyltriacetoxysilane (17689-77-9), Polydimethylsiloxane (63148-62-9). Pennsylvania Right-to-Know (Non-Haz @ >3%): Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ingredients Known to State of California to cause birth defects or reproductive harm: None. NFPA Profile: Health: 2, Flammability: 1, Reactivity: 0. Note: Silicone sealant colors, other than white, may contain a small amount of Carbon Black (1333-86-4). INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

<u>LEGEND</u>: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act, NFPA – National Fire Protection Association.

Reviewed By: Larry G. Brandon VP Technology & General Manager March 12, 2012

NAME TITLE DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.