



PIPE INSULATION

Product Highlights

Our closed-cell polyethylene hot water Pipe Insulation is used to insulate residential and commercial hot water, non-steam pipes providing improved thermal efficiency. Insulating hot water pipes reduces heat loss and can raise water temperature 2°F - 4°F and prevents freezing and sweating. Our pipe insulation provides excellent resistance to water and water vapor. The insulation is flexible and easy to install.

Product Details

- 100% pre-slit
- Temperature range -160°F to 200°F
- Available in multiple sizes

Item Code	Description	Dimensions	Case Qty
PIO10	Pipe Insulation	1/2" Wall for 1/2" Copper, 129'/case	43 pcs.
PIO11	Pipe Insulation	1/2" Wall for 3/4" Copper, 84'/case	28 pcs.
PIO12	Pipe Insulation	1/2" Wall for 1" Copper, 60'/case	20 pcs.
PIO13	Pipe Insulation	1/2" Wall for 1-1/4" Copper, 120'/case	40 pcs.
PIO14	Pipe Insulation	1/2" Wall for 1-1/2" Copper, 36'/case	12 pcs.
PIO15	Pipe Insulation	1/2" Wall for 2" Copper, 27'/case	9 pcs.
PIO16	Pipe Insulation	3/4" Wall for 3/4" Copper, 51'/case	17 pcs.
PIO18	Pipe Insulation	3/4" Wall for 1/2" Copper, 72'/case	24 pcs.

Certification and Performance Requirements

- ASTM E 84 1" 25/50

