



## Manufacturers Fact Sheet

This fact sheet contains important details about Owens Corning's™ ProCat™ PINK® FIBERGLAS™ Insulation. Read it carefully.

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the label minimum thickness. Installation

of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required number of bags and at least the minimum thickness will result in lower insulation R-value.

### Read This Before You Buy

#### What you should know about R-Values

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate, the type and size of your home, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

### ProCat™ (attic)

Nominal bag weight 33.5 lbs.

R Value	Bags per 1000 Sq.Ft.	Maximum Net Coverage, Sq. Ft.	Minimum Weight/ Sq. Ft.	Minimum Thickness, inches	Minimum Settled Thickness, Inches
13	5.1	196.5	0.169	4.75	4.75
19	7.8	127.8	0.260	7.00	7.00
22	9.1	109.8	0.303	8.00	8.00
26	10.7	93.5	0.358	9.25	9.25
30	12.5	80.0	0.416	10.50	10.50
38	16.5	60.5	0.550	13.25	13.25
44	19.3	51.9	0.641	15.00	15.00
49	21.7	46.1	0.722	16.50	16.50
60	27.3	36.6	0.908	19.75	19.75

### ProCat™ (walls)

Nominal bag weight 33.5 lbs.

R Value	Minimum Bags per 100 sq. ft	Maximum Coverage Per Bag in Sq. Ft	Minimum Weight in Lb / Sq. Ft.	Minimum Initial Installed Thickness in Inches	Installed Density lb per cubic foot
14	11.3	90.2	0.379	3.5	1.3
15	13.1	78.1	0.438	3.5	1.5
22	17.8	57.4	0.596	5.5	1.3
24	24.7	41.4	0.825	5.5	1.8

Please contact 419-248-6557 for additional information. Email: [gettech@owenscorning.com](mailto:gettech@owenscorning.com)

#### Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



**OWENS CORNING INSULATING SYSTEMS, LLC**  
ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO, USA 43659  
**1-800-GET-PINK®**  
[www.owenscorning.com](http://www.owenscorning.com)

Pub. No. 10019591. Printed in U.S.A. February 2015. THE PINK PANTHER™ & © 1964–2015 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2015 Owens Corning. All Rights Reserved.

