



Material Safety Data Sheet

Dow Chemical Canada ULC

Product Name: FROTH-PAK(TM) 620 AF HFC ISO Spray Foam Sealant

Issue Date: 2010.02.25

Print Date: 04 Dec 2010

Dow Chemical Canada ULC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Product and Company Identification

Product Name

FROTH-PAK(TM) 620 AF HFC ISO Spray Foam Sealant

COMPANY IDENTIFICATION

Dow Chemical Canada ULC
A Subsidiary of The Dow Chemical Company
4445 Marie-Victorin Blvd
Varenes, QC J3X 1T3
Canada

For MSDS updates and Product Information: 800-331-6451

Prepared By: Prepared for use in Canada by EH&S, Hazard Communications.
Revision 2010.02.25
Print Date: 12/4/2010

Customer Information Number: 800-331-6451

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: (989) 636-4400
Local Emergency Contact: 989-636-4400

2. Hazards Identification

Emergency Overview

Color: Brown

Physical State: Liquid.

Odor: Musty

Hazards of product:

WARNING! May cause eye irritation. May cause skin irritation. May cause allergic skin reaction. May cause allergic respiratory reaction. Vapor reduces oxygen available for breathing. May cause central nervous system effects. Keep upwind of spill. May cause anesthetic effects. May cause respiratory tract irritation. May cause lung injury. May react with water. Stay out of low areas. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction. Toxic fumes may be released in fire situations. Contents under pressure.

Potential Health Effects

Eye Contact: May cause moderate eye irritation. May cause slight temporary corneal injury.

Skin Contact: Prolonged contact may cause skin irritation with local redness. May stain skin.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Skin Sensitization: Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

Inhalation: In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause central nervous system effects. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

Respiratory Sensitization: May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Observations in animals include: Gastrointestinal irritation.

Aspiration hazard: Based on available information, aspiration hazard could not be determined.

Effects of Repeated Exposure: Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Cancer Information: Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Birth Defects/Developmental Effects: In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother. Based on information for component(s): 1,1,1,2-Tetrafluoroethane. Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

3. Composition/information on ingredients

Component	CAS #	Amount W/W
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>= 60.0 - <= 100.0 %
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 30.0 - <= 60.0 %
1,1,1,2-Tetrafluoroethane	811-97-2	>= 5.0 - <= 10.0 %

Amounts are presented as percentages by weight.

Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

4. First-aid measures

Eye Contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Eye wash fountain should be located in immediate work area.

Skin Contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Medical Conditions Aggravated by Exposure: Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

Emergency Personnel Protection: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

5. Fire Fighting Measures

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Do not use direct water stream. May spread fire. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Unusual Fire and Explosion Hazards: Some components of this product will burn in a fire situation. Product reacts with water. Reaction may produce heat and/or gases. This reaction may be violent. Container may rupture from gas generation in a fire situation. Blowing agent vaporizes quickly at room temperature. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Isocyanates. Hydrogen cyanide. Carbon monoxide. Carbon dioxide. Hydrogen halides. Halogenated hydrocarbons.

See Section 9 for related Physical Properties

6. Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Contain spilled material if possible. Absorb with materials such as: Vermiculite. Dirt. Sand. Clay. Do NOT use absorbent materials such as: Cement powder (Note: may generate heat). Collect in suitable and properly labeled open containers. Do not place in sealed containers. Suitable containers include: Metal drums. Plastic drums. Polylined fiber pacs. Wash the spill site with large quantities of water. Attempt to neutralize by adding suitable decontaminant solution: Formulation 1: sodium carbonate 5 - 10%; liquid detergent 0.2 - 2%; water to make up to 100%, OR Formulation 2: concentrated ammonia solution 3 - 8%; liquid detergent 0.2 - 2%; water to make up to 100%. If ammonia is used, use good ventilation to prevent vapor exposure. Contact Dow for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

Personal Precautions: Isolate area. Ventilate area of leak or spill. Keep personnel out of low areas. Keep upwind of spill. Keep unnecessary and unprotected personnel from entering the area. If available, use foam to smother or suppress. Refer to Section 7, Handling, for additional precautionary measures. See Section 10 for more specific information. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash thoroughly after handling. Keep container tightly closed. Contents under pressure. Do not puncture or incinerate container. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Do not enter confined spaces unless adequately ventilated. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Storage

Store under cover in a dry, clean, cool, well ventilated place away from sunlight. Do not store product contaminated with water to prevent potential hazardous reaction.

Storage Period:

15 Months

Storage temperature:

24 °C

8. Exposure Controls / Personal Protection

Exposure Limits

Component	List	Type	Value
4,4' -Methylenediphenyl diisocyanate	ACGIH	TWA	0.005 ppm

	CAD AB OEL	TWA	0.051 mg/m3 0.005 ppm
	CAD BC OEL	TWA	0.005 ppm SKIN
	CAD BC OEL	CEILING	0.01 ppm SKIN
	CAD ON OEL	TWAEV	0.005 ppm
	CAD ON OEL	CEV	0.02 ppm
	OEL (QUE)	TWA	0.051 mg/m3 0.005 ppm SEN Exposure must be minimized.
Diphenylmethane Diisocyanate, isomers and homologues	CAD AB OEL	TWA	0.07 mg/m3 0.005 ppm
	CAD BC OEL	TWA	0.005 ppm
	CAD BC OEL	CEILING	0.01 ppm
1,1,1,2-Tetrafluoroethane	AIHA WEEL	TWA	4,240 mg/m3 1,000 ppm

Consult local authorities for recommended exposure limits.

A "skin" notation following the inhalation exposure guideline refers to the potential for dermal absorption of the material including mucous membranes and the eyes either by contact with vapors or by direct skin contact.

It is intended to alert the reader that inhalation may not be the only route of exposure and that measures to minimize dermal exposures should be considered.

A "SEN" notation following the exposure guideline refers to the potential to produce sensitization, as confirmed by human or animal data.

Personal Protection

Eye/Face Protection: Use chemical goggles. Eye wash fountain should be located in immediate work area.

Skin Protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before reuse or dispose of properly. Items which cannot be decontaminated, such as shoes, belts and watchbands, should be removed and disposed of properly.

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene. Chlorinated polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton. Neoprene. Polyvinyl chloride ("PVC" or "vinyl"). Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are

inadequate to warn of excessive exposure. Lethal concentrations may exist in areas with poor ventilation.

9. Physical and Chemical Properties

Physical State	Liquid.
Color	Brown
Odor	Musty
Odor Threshold	No test data available
Flash Point - Closed Cup	Not applicable
Flammability (solid, gas)	Not applicable to liquids
Flammable Limits In Air	Lower: No test data available Upper: No test data available
Autoignition Temperature	No test data available
Vapor Pressure	240 psi @ 23 °C <i>Estimated</i> . Container is under pressure.
Boiling Point (760 mmHg)	No test data available.
Vapor Density (air = 1)	No test data available
Specific Gravity (H2O = 1)	1.24 <i>Estimated</i> .
Freezing Point	No test data available
Melting Point	No test data available
Solubility in water (by weight)	insoluble, reacts, evolution of CO2
pH	Not applicable
Decomposition Temperature	No test data available
Partition coefficient, n-octanol/water (log Pow)	No data available for this product. See Section 12 for individual component data.
Evaporation Rate (Butyl Acetate = 1)	No test data available
Kinematic Viscosity	No test data available

10. Stability and Reactivity

Stability/Instability

Stable under recommended storage conditions. See Storage, Section 7.

Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Elevated temperatures can cause pressure buildup in closed containers due to the release of blowing agents. Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid. Avoid moisture. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

Incompatible Materials: Avoid contact with: Acids. Alcohols. Amines. Water. Ammonia. Bases. Metal compounds. Moist air. Strong oxidizers. Diisocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the diisocyanate. Diisocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat. Avoid contact with metals such as: Aluminum. Zinc. Brass. Tin. Copper. Galvanized metals. Avoid contact with absorbent materials such as: Moist organic absorbents. Avoid unintended contact with polyols. The reaction of polyols and isocyanates generate heat.

Hazardous Polymerization

Can occur. Elevated temperatures can cause hazardous polymerization. Polymerization can be catalyzed by: Strong bases. Water.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition.

11. Toxicological Information

Acute Toxicity

Ingestion

Single dose oral LD50 has not been determined. Estimated. LD50, Rat > 10,000 mg/kg

Dermal

The dermal LD50 has not been determined. Estimated. LD50, Rabbit > 2,000 mg/kg

Inhalation

The LC50 has not been determined. Estimated. LC50, Aerosol, Rat > 490 mg/m3

Serious eye damage/eye irritation

May cause moderate eye irritation. May cause slight temporary corneal injury.

Skin corrosion/irritation

Prolonged contact may cause skin irritation with local redness. May stain skin.

Sensitization

Skin

Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

Respiratory

May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Repeated Dose Toxicity

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Chronic Toxicity and Carcinogenicity

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m3) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Developmental Toxicity

In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother. Based on information for component(s): 1,1,1,2-Tetrafluoroethane. Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Reproductive Toxicity

No relevant information found.

Genetic Toxicology

Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

12. Ecological Information

ENVIRONMENTAL FATE

Data for Component: Diphenylmethane Diisocyanate, isomers and homologues

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: 4,4' -Methylenediphenyl diisocyanate

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: 1,1,1,2-Tetrafluoroethane

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is high (Koc between 50 and 150).

Henry's Law Constant (H): 5.00E-02 atm*m3/mole; 25 °C Measured

Partition coefficient, n-octanol/water (log Pow): 1.68 Estimated.

Partition coefficient, soil organic carbon/water (Koc): 97 Estimated.

Persistence and Degradability

1,1,1,2-Tetrafluoroethane (HFC-134a) has a stratospheric ozone depletion potential (ODP) of zero, relative to CFC 12 (ODP=1). Material is expected to biodegrade only very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
6.20E-15 cm3/s	1,700 d	Estimated.

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
4 %	28 d	OECD 301D Test

Theoretical Oxygen Demand: 0.47 mg/mg

ECOTOXICITY

Data for Component: Diphenylmethane Diisocyanate, isomers and homologues

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: 4,4' -Methylenediphenyl diisocyanate

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: 1,1,1,2-Tetrafluoroethane

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (*Oncorhynchus mykiss*), static, 96 h: 450 mg/l
Aquatic Invertebrate Acute Toxicity
EC50, water flea *Daphnia magna*, 48 h, immobilization: 980 mg/l

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. Transport Information

TDG Small container

Proper Shipping Name: COMPRESSED GAS, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956

TDG Large container

Proper Shipping Name: COMPRESSED GASES, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956

IMDG

Proper Shipping Name: COMPRESSED GASES, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956

EMS Number: F-C,S-V

ICAO/IATA

Proper Shipping Name: COMPRESSED GAS, N.O.S.

Technical Name: Fluorinated Hydrocarbons, Nitrogen

Hazard Class: 2.2 **ID Number:** UN1956 **Cargo Packing Instruction:** 200

Passenger Packing Instruction: 200

15. Regulatory Information

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

Hazardous Products Act Information: CPR Compliance

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Hazardous Products Act Information: WHMIS Classification

A	Compressed Gas
D2A	Respiratory Tract Sensitizer
D2B	Eye or Skin Irritant
D2B	Skin Sensitizer

Hazardous Products Act Information: Hazardous Ingredients

This product contains the following ingredients which are Controlled Products and/or are on the Ingredient Disclosure List (Canadian HPA Section 13 and 14).

Component	CAS #	Amount W/W
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 30.0 - <= 60.0 %

16. Other Information

Recommended Uses and Restrictions

Component(s) for the manufacture of urethane polymers.

Revision

Identification Number: 1041164 / 1002 / Issue Date 2010.02.25 / Version: 2.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ DES	Hazard Designation
VOL/VOL	Volume/Volume

Dow Chemical Canada ULC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.