

# Silirub HT1

**SOUDAL**

- 100% RTV Silicone
- High Temp Silicone, Withstands Temperatures Up to Intermittent Heat of 500°F
- Red In Color
- Excellent Adhesion to Glass, Ceramic, Porcelain, Metals, Wood & Many More
- Permanently Elastic
- Watertight & Airtight
- Easy to Apply & Easy Clean-up
- UV Resistant
- Meets ASTM C-920, Type S, Grade NS, Class 25
- Complies With FDA Regulations 21 CFR Section 177.2600: "Rubber Articles Intended For Repeated Use"

**HVAC/R**  
**Heating Elements**  
**Vents & Pipes**



This information and all further technical advice are based on SOUDAL present knowledge and experience. However, SOUDAL assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. SOUDAL disclaims all WARRANTIES EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. SOUDAL SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. SOUDAL reserves the right to make any changes according to technological progress or further developments.

# SOUDAL

(\*) These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. Test results are averages obtained under laboratory conditions. Reasonable variations can be expected.

- This product is not paintable.
- This product is not to be used as a structural glazing sealant.
- We always recommend a preliminary adhesion test on every surface.
- Lower temperatures and humidity will extend curing time.

KEEP OUT OF REACH OF CHILDREN. Avoid skin and eye contact. On contact, uncured sealant could cause irritation to skin and eyes. In case of eye contact, flush eyes with warm water for 15 minutes, call a physician. For skin contact, remove sealant with a paper towel. If swallowed, do not induce vomiting, call a physician. Silirub HT1 is manufactured for professional use only. Refer to Safety Data Sheet (SDS) for further information

## SOUDAL FEATURES

