LED A19 OMNI

9 Watt 2700K - Retail Pack A19 OMNI LED





Electrical						
Watt	9					
Input Current	104 (mA)					
Power Factor	> 0.50					
Voltage	120 volt					
Frequency	60hz					
Min. Start Temp	-4F					
Max. Operating Temp	104F					
Base Type	E26 Medium					
Light						
Initial Lumens	810					
Lumens per Watt	90					
Color Temperature	2700K					
Color Rendering (CRI)	81					
Beam Angle	Omni-Directional					
Agency Approvals						
UL	Yes					
Energy Star	25,000 rated hours					
RoHS	Yes					
FCC	Yes					
Product Details						
Warranty	10 years, 6 hrs/day					
Mercury Content	0					
Diameter	2.3622"					
Overall Length	4.6457"					

PRODUCT DESCRIPTION

9 watt A19 Omni-directional EarthBulb LED provides 810 lumens and replaces 60 watt incandescent bulbs for over 75% energy savings. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. Energy Star rated product. May be used in fully enclosed fixtures.

PRODUCT FEATURES

- This A bulb is Energy Star and provides 810 lumens, capable of dimming to less than 5%
- ≥300° beam angle provides full radial illumination
- Chipset provides 2700K soft white light with a high color rendering rating of over 81
- New heat sync system provides improved aesthetics and performance


PRODUCT APPLICATIONS



LUMINOUS DISTRIBUTION INTENSITY DATA


Y(deg)					
C(deg)	0	23	45	68	90
0	82.9	82.8	82.7	82.6	82.5
5	82.9	82.7	82.6	82.4	82.3
10	82.8	82.7	82.6	82.5	82.5
15	82.9	82.8	82.8	82.8	82.8
20	83.1	83.0	82.9	82.9	83.0
25	83.3	83.2	83.1	83.1	83.2
30	83.7	83.5	83.4	83.4	83.5
35	84.1	83.8	83.6	83.6	83.7
40	84.3	84.0	83.7	83.7	83.8
45	84.4	84.0	83.7	83.7	83.8
50	84.4	83.9	83.5	83.4	83.6
55	84.1	83.6	83.1	83.0	83.2
60	83.6	83.0	82.5	82.3	82.5
65	82.9	82.2	81.6	81.4	81.7
70	82.0	81.3	80.6	80.3	80.6
75	80.9	80.0	79.3	79.0	79.3
80	79.5	78.6	77.8	77.5	77.7
85	77.8	76.9	76.1	75.7	76.0
90	75.9	75.0	74.1	73.7	74.0

LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):289.6°

Note: IES files available upon request.





MODEL NUMBER: LA19927D6

Order Code	Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty		
10258	1	840791102589	00840791102589	12	84079110258900	48		
Dimensions (inches - Length x Width x Height)								
10258	1	2.56 x 2.56 x 5.11	10.78 x 8.15 x 5.78	12	22.36 x 17.08 x 7.13	48		
Weight (lbs)								
10258	1	0.4136	3.92	12	16.53	48		





