LED A19 OMNI



Electrical					
Watt	11				
Input Current	104 (mA)				
Power Factor	> 0.90				
Voltage	120 volt				
Frequency	60hz				
Min. Start Temp	-4F				
Max. Operating Temp	104F				
Base Type	E26 Medium				
Light					
Initial Lumens	1100				
Lumens per Watt	100				
Color Temperature	2700K				
Color Rendering (CRI)	81				
Beam Angle	Omni Directional				
Agency Approvals					
UL	Yes, UL1993 Enclosed Fixture				
Energy Star V2.0	15,000 rated hours				
RoHS	Yes				
FCC	Yes				
Product Details					
Warranty	5 years, 6 hrs/day				
Mercury Content	0				
Diameter	2.3622"				
Overall Length	4.6457"				

1100 Lumen 11 Watt 2700K A19 OMNI LED - Commercial Pack



PRODUCT DESCRIPTION


11 watt A19 Omni-directional EarthBulb LED provides 1100 lumens and replaces 75 watt incandescent directional bulbs for over 80% energy savings. 2700K color of light is standard. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. Energy Star rated product. Suitable for outdoor use, damp location, when installed in fixtures and not directly exposed to weather.

PRODUCT FEATURES

- This A bulb is Energy Star and provides 1100 lumens, capable of dimming to less than 5%
- Omni directional beam angle provides full radial illumination
- Chipset provides 2700K soft light with a high color rendering rating of over 81
- New heat sync system provides improved aesthetics and performance
- Suitable for outdoor use, damp location, when installed in fixtures and not directly exposed to weather



LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):225.3°

Note: IES files available upon request.



Individual





MODEL NUMBER: LA191127V2

Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty		
1	840791103319	00840791103319	12	84079110331900	48		
Dimensions (inches - Length x Width x Height)							
1	2.48 x 2.48 x 4.72	10.47 x 7.91 x 5.39	12	21.73 x 16.61 x 6.73	48		
Weight (lbs)							
1	0.39	3.02	12	12.89	48		
	1	1 840791103319 ength x Width x Height) 1 2.48 x 2.48 x 4.72	1 840791103319 00840791103319 ength x Width x Height) 1 2.48 x 2.48 x 4.72 10.47 x 7.91 x 5.39	1 840791103319 00840791103319 12 ength x Width x Height) 1 2.48 x 2.48 x 4.72 10.47 x 7.91 x 5.39 12	1 840791103319 00840791103319 12 84079110331900 ength x Width x Height) 1 2.48 x 2.48 x 4.72 10.47 x 7.91 x 5.39 12 21.73 x 16.61 x 6.73		



