# LED BR30







| Electrical               |                     |  |  |
|--------------------------|---------------------|--|--|
| Watt                     | 12.5                |  |  |
| Input Current            | 120 (mA)            |  |  |
| Power Factor             | > 0.70              |  |  |
| Voltage                  | 120 volt            |  |  |
| Frequency                | 60hz                |  |  |
| Min. Start Temp          | -4F                 |  |  |
| Max. Operating<br>Temp   | 104F                |  |  |
| Base Type                | E26 Medium          |  |  |
| Light                    |                     |  |  |
| Initial Lumens           | 800                 |  |  |
| Lumens per Watt          | 64                  |  |  |
| Color Temperature        | 3000K               |  |  |
| Color Rendering<br>(CRI) | 92                  |  |  |
| Beam Angle               | 110°                |  |  |
| Agency Approvals         |                     |  |  |
| UL                       | Yes                 |  |  |
| Energy Star              | 25,000 hr rated     |  |  |
| RoHS                     | Yes                 |  |  |
| FCC                      | Yes                 |  |  |
| CEC                      | Yes                 |  |  |
| Product Details          |                     |  |  |
| Warranty                 | 10 years, 6 hrs/day |  |  |
| Mercury Content          | 0                   |  |  |
| Diameter                 | 3.7402"             |  |  |
| Overall Length           | 5.31"               |  |  |

#### PRODUCT DESCRIPTION

12.5 watt BR30 EarthBulb LED floodlight replaces 65 watt incandescent floodlights which may provide 80% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. Multi-Chipset high power LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. Energy Star rated product and meets California Energy Commission standards.

#### **PRODUCT FEATURES**

- Dimming BR30 flood light is provides 800 lumens, capable of dimming to less than 5%
- Full 110° beam angle provides full radial illumination
- · Chipset provides 3000K white light with a high color rendering rating of over 90

## PRODUCT APPLICATIONS



### MODEL NUMBER: LBR31230D

| Order Code          | Individual UPC     | Master Park UPC      | Qty |
|---------------------|--------------------|----------------------|-----|
| 10274               | 840791102749       | 00840791102749       | 12  |
| Dimensions (inches) |                    |                      |     |
| 10274               | 4.06 x 4.06 x 6.69 | 17.32 x 13.15 x 7.40 | 12  |
| Weight (lbs)        |                    |                      |     |
| 10274               | 0.682              | 7.40                 | 12  |



Individual





