



## Outswing Entry Steel Door


Series 5500

### Standard Features

- White painted galvanized steel mounting frame
- 1-3/8" door thickness
- Core is edged bored, capped and face drilled for dead bolt
- Cottage style (9 light) window option available
- Full perimeter compression gaskets and seals
- 6-Panel design
- Polystyrene foam core insulation
- 4 extruded hinges with bushings
- Manufactured to comply with HUD Std. 3280-405



**Extruded Hinge**



**Gasket & Seal**



A totally efficient thermal entrance system. Completely pre-hung and ready to install, with optional storm doors available to order



## Available Styles for Series 5500 Outswing Steel Entry Doors

Contact your sales representative for the full line of door styles.



6-Panel



Cottage

### Standard Sizes

Call sizes are the same as rough opening sizes. Rough opening must be exact (+ or -) 1/8"

- 32 x 72
- 32 x 76
- 34 x 72
- 34 x 76
- 34 x 80
- 36 x 76

It is the responsibility of the owner, architect, or builder to make product selections that are in compliance with applicable laws and building codes.

2016 Kinro® Inc. all rights reserved. Due to continuous product improvement, Kinro reserves the right to make changes including, and not limited to, design, accessories, colors and pricing without notice or obligation. Some details shown separately, or on products illustrated in this literature, may be optional at extra cost. Your Kinro sales representative is always the best source of current information.



STYLECREST®

Style Crest, Inc.  
2450 Enterprise St.  
Fremont, Ohio 43420



Printed in U.S.A.

Specifications subject to change without notice © Copyright 2016 Rev. 09/02/16 MH-0049