



Corporate Headquarters  
4381 West Green Oaks  
Blvd. Suite 200  
Arlington, TX 76016  
817-483-7791

## 9770 VINYL WINDOW FEATURES

Vinyl construction provides high thermal performance.

Frame and sash corners are welded for added strength and water tight corners.

Frame designed with multiple hollow areas for maximum strength and energy efficiency.

Positive integral lock at the meeting rail for increased home security and weather resistance.

Dual weather seal to reduce drafts and enhance energy performance.

Nominal 3/4" insulating glass provides superior thermal performance.

Integral "J" trim eliminates the need for additional exterior frame accessories and covers the raw edge of the siding for a clean appearance.

Deep pocket sill for added window strength and weather resistance.

Both window sashes can be tilted in and removed for easy cleaning.

Beveled frame for attractive, sleek appearance.

Metal reinforcement in the meeting rails provide added strength.

Extruded aluminum screen rail adds strength and stability eliminating the need for installation clips or bands.

The aluminum screen rail also provides an additional interlock leg that adds strength to the entire unit.

Spiral balances in both sashes provide near effortless operation.



9770 DOUBLE HUNG VINYL WINDOW

Kinro Inc. reserves the right to change details or sizes without notice. The customer assumes all risk for alterations made to Kinro products.  
All Kinro primary window products are laboratory tested to meet or exceed all manufactured housing federal specifications as labeled on each window.  
AAMA 1701 compliant for Housing and Urban Development (HUD) codes. AAMA 101 compliant for residential building code requirements.  
Able to meet Energy Star requirements in all 50 states.

[www.kinro.com](http://www.kinro.com)