

# Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

1 Identification	
· Product identifier	
· Trade name: <u>Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B</u> · Other product identifiers: EHS 2522 B	
<ul> <li>Recommended use and restriction on use</li> <li>Recommended use: Polyurethane resin</li> <li>Restrictions on use: No relevant information available.</li> </ul>	
<ul> <li>Details of the supplier of the Safety Data Sheet</li> <li>Manufacturer/Supplier: Convenience Products</li> <li>866 Horan Drive</li> <li>Pacific, MO 63026</li> <li>Phone: 636-349-5855</li> <li>Toll-Free: 1-800-325-6180</li> </ul>	
<ul> <li>Emergency telephone number: ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)</li> </ul>	
2 Hazard(s) identification	
<ul> <li>Classification of the substance or mixture</li> <li>Press. Gas H280 Contains gas under pressure; may explode if heated.</li> </ul>	
Acute Tox. 4 H302 Harmful if swallowed.	
Skin Irrit. 2 H315 Causes skin irritation.	
Eye Irrit. 2A H319 Causes serious eye irritation.	
STOT SE 3 H335 May cause respiratory irritation.	
<ul> <li>Label elements</li> <li>GHS label elements</li> <li>The product is classified and labeled according to the Globally Harmonized System (GHS).</li> <li>Hazard pictograms:</li> <li>GHS04 GHS07</li> </ul>	
<ul> <li>Signal word: Warning</li> <li>Hazard statements: H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation.</li> <li>Precautionary statements: P233 Keep container tightly closed. P261 Avoid breathing mist, vapors, or spray. P264 Wash thoroughly after handling.</li> </ul>	

(Cont'd. on page 2)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

	(Cont'd. of page 1)
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
• Other hazards T	There are no other hazards not otherwise classified that have been identified.

# 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

# · Components:

Г

	Polyether polyol	25-50%
	1 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
811-97-2	Norflurane Press. Gas, H280 Simple Asphyxiant	10-25%
13674-84-5	tris(2-chlorisopropyl)-phosphate  Acute Tox. 4, H302	10-25%
52019-35-9	Methyloxirane polymer with oxirane, ether with 2,6-bis[(bis(2-hydroxyethyl)amino) methyl]-4-nonylphenol (5:1) Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315	<10%
68441-62-3	halogenated aliphatic polyether polyol 🚯 Acute Tox. 4, H302; Eye Irrit. 2A, H319	<10%
9016-45-9	nonylphenol, ethoxylated Skin Irrit. 2, H315; Eye Irrit. 2A, H319	<10%
	halogenated hydrocarbon Flam. Liq. 2, H225 Acute Tox. 4, H332	<10%

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 3)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

# Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 2)

	d measures
	tion of first aid measures
After inh	
	esh air; consult doctor in case of complaints.
	f unconsciousness place patient stably in side position for transportation.
	n contact:
	Ill solidified product away from the skin.
	ely wash with water and soap and rinse thoroughly. tation continues, consult a doctor.
	e contact:
	contact lenses if worn.
	ened eye for several minutes under running water. If symptoms persist, consult a doctor.
After sw	
	oute of exposure.
	mouth and then drink plenty of water.
	duce vomiting; immediately call for medical help.
Most im	portant symptoms and effects, both acute and delayed:
Headach	
Coughing	
Dizziness	
	skin and mucous membranes.
	ye irritation.
	e respiratory irritation.
	Harmful if swallowed.
	n of any immediate medical attention and special treatment needed: upervision for at least 48 hours.
	ary oxygen respiration treatment.
II HECE33	
Fire-fig	hting measures
	ishing media
	extinguishing agents:
	nguishing powder or water spray. Fight larger fires with water spray.
	y reasons unsuitable extinguishing agents: None.
	hazards arising from the substance or mixture
	f receptacles bursting because of high vapor pressure if heated. n of toxic gases is possible during heating or in case of fire.
	for firefighters
	re equipment:
	f-contained respiratory protective device. y protective suit.

Additional information: Cool endangered receptacles with water spray.

(Cont'd. on page 4)



# Convenience products

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

## Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 3)

# 6 Accidental release measures

# · Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

#### **Environmental precautions**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

Organic solvent

#### **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

### <sup>·</sup> Handling

• Precautions for safe handling:

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

Keep out of reach of children.

#### Information about protection against explosions and fires:

Keep respiratory protective device available.

Do not spray on a naked flame or any incandescent material.

## <sup>•</sup> Conditions for safe storage, including any incompatibilities

- · Storage
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers. Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

## • Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Specific end use(s) No relevant information available.

(Cont'd. on page 5)



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 4)

8 Exposure co	ontrols/personal protection
•	
· Control parar	vith limit values that require monitoring at the workplace:
811-97-2 Norflu	
WEEL (USA)	Long-term value: 1000 ppm
, ,	-dichloroethylene
PEL (USA)	Long-term value: 790 mg/m <sup>3</sup> , 200 ppm
REL (USA)	Long-term value: 790 mg/m³, 200 ppm
TLV (USA)	Long-term value: 790 mg/m³, 200 ppm
EL (Canada)	Long-term value: 200 ppm
EV (Canada)	Short-term value: 990 mg/m <sup>3</sup> , 250 ppm
	Long-term value: 790 mg/m <sup>3</sup> , 200 ppm
LMPE (Mexico)	Long-term value: 200 ppm
Keep away from Immediately rer Wash hands be Avoid contact w Engineering co Breathing equi Use suitable res Use suitable res Protection of h	spiratory protective device in case of insufficient ventilation. spiratory protective device when high concentrations are present.
	rial has to be impermeable and resistant to the product/ the substance/ the preparation.
Safety	glasses
Limitation an No relevant info	on: Protective work clothing d supervision of exposure into the environment ormation available. ment measures See Section 7 for additional information.

(Cont'd. on page 6)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

# Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 5)

Physical and chemical prope	rties	
Information on basic physical a	nd chemical properties	
· Appearance:		
Form:	Aerosol	
Color:	Amber colored	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Melting point/Melting range:	Not applicable, as aerosol.	
<ul> <li>Boiling point/Boiling range:</li> </ul>	-26 °C (-15 °F)	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	>260 °C (>500 °F)	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Not determined.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
<sup>·</sup> Vapor pressure at 20 °C (68 °F):	5716 hPa (4287 mm Hg)	
· Density:		
Relative density:	1.14	
Vapor density:	Not determined.	
Evaporation rate:	Not applicable.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC content:	3.2% / 27.8 g/l (US EPA Method 24)	
• Other information	No relevant information available.	

# 10 Stability and reactivity

· Reactivity: No relevant information available.

· Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapor pressure if heated.

Possibility of hazardous reactions

Reacts with peroxides.

(Cont'd. on page 7)



## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 6)

Reacts with catalysts. Reacts with strong acids and oxidizing agents. Exothermic polymerization.

• Conditions to avoid Excessive heat and contact with oxidizers.

· Incompatible materials Oxidizers

· Hazardous decomposition products

Carbon monoxide and carbon dioxide Phosphorus compounds Nitrogen oxides (NOx) Chlorine compounds

# 11 Toxicological information

<sup>·</sup> Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

13674-84-5 tris(2-chlorisopropyl)-phosphate

Oral LD50 1101 mg/kg (rat)

68441-62-3 halogenated aliphatic polyether polyol

Oral LD50 1337 mg/kg (rat)

9016-45-9 nonylphenol, ethoxylated

Oral LD50 4290 mg/kg (mouse)

Primary irritant effect:

· On the skin: Irritant to skin and mucous membranes.

• On the eye: Irritating effect.

• Sensitization: Based on available data, the classification criteria are not met.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

• NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Inhalation.

Eye contact.

Skin contact.

• Acute effects (acute toxicity, irritation and corrosivity):

Harmful if swallowed.

Irritating to eyes, respiratory system and skin.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity: Based on available data, the classification criteria are not met.

• Carcinogenicity: Based on available data, the classification criteria are not met.

• **Reproductive toxicity:** Based on available data, the classification criteria are not met.

• STOT-single exposure: May cause respiratory irritation.

(Cont'd. on page 8)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

#### Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 7)

STOT-repeated exposure: Based on available data, the classification criteria are not met.
 Aspiration hazard: Based on available data, the classification criteria are not met.

# 12 Ecological information

- <sup>·</sup> Toxicity
- · Aquatic toxicity

Harmful to aquatic life with long lasting effects.

#### 13674-84-5 tris(2-chlorisopropyl)-phosphate

LC50 51 mg/l (pimephales promelas)

EC50 131 mg/l (daphnia)

9016-45-9 nonylphenol, ethoxylated

LC50 1.821 mg/l (daphnia) (48 h)

Persistence and degradability The product is partially biodegradable. Significant residuals remain.
 Bioaccumulative potential: May be accumulated in organism

• Mobility in soil: No relevant information available.

- Ecotoxical effects:
- · Remark:
- Harmful to fish

Due to mechanical actions of the product (e.g. agglutinations), damages may occur.

Additional ecological information

· General notes: Avoid release to the environment.

- <sup>•</sup> Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No relevant information available.

# 13 Disposal considerations

## <sup>·</sup> Waste treatment methods

#### · Recommendation:

Contact manufacturer for recycling information.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

# <sup>·</sup> Uncleaned packagings

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

(Cont'd. on page 9)



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

# Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 8)

UN-Number DOT, ADR, IMDG, IATA	UN3500
UN proper shipping name DOT, IATA	Chemical under pressure, n.o.s. (Fluorinat hydrocarbon, Nitrogen)
ADR, IMDG	CHEMICAL UNDER PRESSURE, N.O. (FLUORINATED HYDROCARBON, NITROGEN)
Transport hazard class(es)	
DOT	
<del></del>	
Class	2.2
Label	2.2
<b>~</b>	
Class	2 8A Gases
Label IMDG, IATA	2.2
<del></del>	
Class	2 Gases
Label	2.2
Packing group	This UN-number is not assigned a packing group.
Environmental hazards	
Marine pollutant:	No
Special precautions for user	Warning: Gases
Danger code (Kemler): EMS Number:	20 F-C,S-V
Transport in bulk according to Annex	

(Cont'd. on page 10)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

45 Degulaters information

Revision: April 11, 2017

# Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 9)

mix	ety, health and environmental regulations/legislation specific for the substance
Uni SAF	ted States (USA) RA
	tion 302 (extremely hazardous substances):
Nor	e of the ingredients are listed.
	tion 355 (extremely hazardous substances):
Nor	e of the ingredients are listed.
Sec	tion 313 (Specific toxic chemical listings):
Nor	e of the ingredients are listed.
TSC	CA (Toxic Substances Control Act)
All i	ngredients are listed.
	position 65 (California)
Che	micals known to cause cancer:
Nor	e of the ingredients are listed.
	micals known to cause reproductive toxicity for females:
Nor	e of the ingredients are listed.
	micals known to cause reproductive toxicity for males:
Nor	e of the ingredients are listed.
Che	micals known to cause developmental toxicity:
	e of the ingredients are listed.
	cinogenic categories
	A (Environmental Protection Agency):
156	-60-5 trans-dichloroethylene
	C (International Agency for Research on Cancer):
Nor	e of the ingredients are listed.
NIO	SH-Ca (National Institute for Occupational Safety and Health):
Nor	e of the ingredients are listed.
Car	adian Domestic Substances List (DSL):
All i	ngredients are listed.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision April 11, 2017 / -

#### · Abbreviations and acronyms:

LDLo: Lowest Lethal Dose Observed

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

(Cont'd. on page 11)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017

Revision: April 11, 2017

### Trade name: Touch 'n Seal Foam Kit CP 1200 FR (1.0pcf) Part B

(Cont'd. of page 10)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health Press. Gas: Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com